

【Product Feature】



- Two ears wearing, enhance comfort and clarity
- The Ultra noise canceling Mic filters 80% background noise
- Hearing protection with Active Protection™ technology
- Ultra Flex™ MIC wires, boom rotation>20k times
- Teflon washer increases stability and ensures optimal durability
- Quick Link(QL™) function
- Optimized for noisy official users and call center users



Specifications】

1. Features			
➤ Receiving Type	Dynamic moving coil	➤ Connection type	Quick Link
➤ Microphone	ECM	➤ Microphone boom	300° adjustable
➤ Wearing Style	Adjustable headband	➤ Comfort aid	Leather/Foam ear cushion
2. Mechanical Specifications			
➤ Weight(without cable)	74g	➤ Contacts	Phosphorbronze gold-plated
➤ Cord length	1.0m	➤ Housing	PA66 Shell Injection
➤ Insertion cycles	10000 minimum	➤ Storage Temperature	- 25℃~65℃
3. Electroacoustical Specifications			
Receiving			
➤ Diameter ϕ	27 mm	➤ THD @ 1kHz	<5%
➤ Rated Frequency Range	Narrow Band(300~3.4 kHz)	➤ Max in-band Distortion	<10%
➤ Nominal Impedance	150 Ω ± 15%	Sealed acoustic press limit @ 1Khz	Measured according to IEC. 318 Standard Audio Test
➤ Sealed Sensitivity @ 1kHz	100±3dB		Measured according to VBeT subjective RX Audio Standard Test(HATS)
Transmitting			
➤ Rated Frequency Range	100-10KHz	➤ Noise canceling (below 1kHz, far field)	Noise canceling
➤ Directivity	Cardioid	➤ Sensitivity @ 1kHz @ 1kHz (RL=2.2K Ω Vs=3.0V DC 0dB=1V/Pa)	-49±3 dB