

2-Port PS/2 KVM Switch Kit TK-205K (v1.4R)

The 2-Port PS/2 KVM Switch Kit lets you manage two PC's with just one set of keyboard, monitor, and mouse. Switch between two PC's with a simple press of a button! The KVM switch includes two separate sets KVM cables and also includes great features such as Auto-Scan, Hot-Key operations, and audio feedback.

PRODUCT OVERVIEW

- 2-port KVM switch with VGA and PS/2 connections to computers
- · Device monitoring with Auto-Scan and audible feedback
- High quality 2048 x 1536 resolution for a crisp display
- · All required cabling included

FEATURES

- · Control up to two computers/servers with one set of console device
- PS/2 keyboard/mouse emulation with 2 sets of detachable KVM cables
- · Compliant with Windows and Linux
- High video quality: up to 2048 x 1536 resolution
- · Auto-scan and LED display for computer monitoring
- · Computer selection by front panel push buttons or keyboard hot key commands.
- · Keyboard status restored when switching between computers
- Plug & play
- · 2-year limited warranty

2-Port PS/2 KVM Switch Kit TK-205K (v1.4R)

SPECIFICATIONS

HARDWARE		
Connections	• 2 computers	
KVM Cables	• 2 sets of 1.2 m (4 ft.) PS/2 KVM cables	
Cable Interface (all male)	To KVM	To Computer
	• 1 x VGA/SVGA HDB 15-pin	 1 x PS/2 keyboard 6-pin mini-DIN 1 x PS/2 mouse 6-pin mini-DIN 1 x VGA/SVGA HDB 15-pin
PC Port Connectors	• 2 x VGA/SVGA HDB 15-pin (female)	
Console Port Connectors (all female)	 1 x PS/2 keyboard 6-pin mini-DIN 1 x PS/2 mouse 6-pin mini-DIN 1 x VGA/SVGA HDB 15-pin 	
Supported OS	Windows and Linux	
Computer Selection	Face panel push buttons or key board hotkey commands	
Auto-Scan Interval	• 10 seconds	
Keyboard State	Save and restore	
Power Type	PS/2 interface power	
Dimensions	• 95 x 65 x 30 mm (3.7 x 2.6 x 1.2 in.)	
Weight	• 85 g (3 oz.)	
Temperature	 Operating: 0°C ~ 40°C (32°F ~104°F) Storage: -20°C ~ 60°C (-4°F ~140°F) 	
Humidity	Max 80% (non-condensing)	
Certifications	• CE, FCC	

NETWORKING SOLUTIONS



PACKAGE CONTENTS

TK-205K

Quick Installation Guide

2 sets of PS/2 KVM cables (1.2 m / 4 ft.)

RELATED PRODUCTS

TK-207K	2-Port USB KVM Switch Kit
TK-208K	2-Port PS/2 KVM Switch Kit with Audio
TK-408K	4-Port PS/2 KVM Switch Kit with Audio

